



ERM-L3360N/ ERM-L3360P

Product Features

- 1/3" Sharp Color CCD
- 600 TVL High Resolution
- 0.2 Lux Color /F2.0 (50IRE)
- 3.7mm Fixed Pinhole lens
- Digital WDR
- OSD Menu, Day- Night, Electronic shutter adjustable, Anti-flicker
- Privacy Zone, Motion Detection, Mirror
- BLC Zones Adjustable
- Metal Housing

Technical Specification

Video	ERM-L3360N	ERM-L3360P
Signal System	NTSC	PAL
CCD	1/3" Sharp Color CCD	
Lens	3.7mm Fixed Pinhole Lens	
Effective Pixel	768 x 494	752 x 582
Horizontal Resolution	600 TVL	
Scanning Frequency (H)	15.734KHz	15.625KHz
Scanning Frequency (V)	59.94KHz	50Hz
Minimum Illumination	0.2 Lux Color / F2.0	
Gamma	0.45 Adjustable	
S/N Ratio	More than 48db	
Video Output	1V p-p, 75 ohms	
Sync System	2:1 Interlace	

Electrical	
Power Supply	12V DC Standard ±10%
Current Consumption	100 mA

Environmental	
Operating Temperature	-10°C ~ 50°C
Humidity	95%

Operational		
Lens	DC / ELC	
Exposure Mode	Auto Flicker/Manual/fixed	
Shutter Speed	AUTO	AUTO
	FLK	FLK
	Fixed 1/60s-1/100,000s	Fixed 1/50s-1/100,000s
AGC	Adjustable	
Digital WDR	Adjustable	
DNR (2 DNR)	Low / Mid / High	
BLC	OFF / BLC / HLC	
Lens Shadow	On / Off	
Day/Night Mode	Auto / BW / Color / EXT	
Mirror	ON / OFF	
Motion Detection	On /Off, Adjustable Zone	
Privacy Masking	On /Off, Adjustable Zone	
Color Control	Brightness, Contrast, Sharpness, Hue & Saturation	
Camera Name	Yes, A to Z, 0 to 9, & etc	
White Balance	Auto / Lock / Manual / Track	

Dimensional	
Housing	Metal
Weight	70g
Dimension	40 x 40 x 15 mm

Note : Product Specifications and Its Contents Subject to change without any prior notice.

