



ERD-R360EN / ERD-R360EP

Product Features

- 1/3" Digital Image Sensor
- High 600 TVL Resolution
- 3.6 mm Fixed Focal Standard Lens
- 0.8 Lux @ f1.2
- Auto Gain Control
- Auto White Balance
- BLC, AES Enabled
- Anti-Flicker Function
- 3 Axis 3.5" Plastic Dome Housing •

Technical Specification

| Video | ERD-R360EN | ERD-R360EP |
|------------------------|---------------------------|------------|
| Signal System | NTSC | PAL |
| Image Sensor | 1/3" Digital Image Sensor | |
| Lens | 3.6 mm M12 Standard Lens | |
| Effective Pixel | 752 x 492 | 768 x 582 |
| Horizontal Resolution | 600 TVL | |
| Minimum Illumination | 0.8Lux @ F1.2 | |
| Scanning Frequency (H) | 15.734KHz | 15.625KHz |
| Scanning Frequency (V) | 59.94KHz | 50Hz |
| Gamma | 0.45 | |
| S/N Ratio | More than 65db | |
| Video Output | 1V p-p, 75W | |
| Sync System | 2:1 Internal | |

| Operational | | |
|---------------|-----------------------|-----------------------|
| IRIS | Electronically | |
| AGC | Auto | |
| BLC | Auto | |
| Exposure Mode | AES | |
| Shutter Speed | Auto 1/60s-1/120,000s | Auto 1/50s-1/120,000s |
| White Balance | ATW | |

| Electrical | |
|---------------------|----------------------|
| Power Supply | 12V DC Standard ±10% |
| Current Consumption | 100mA |

| Dimensional | |
|-------------|--------------------------|
| Housing | 3 Axis 3.5" plastic Dome |
| Weight | 240g |
| Dimension | ∅ 100 * H 80 mm |

| Environmental | |
|-----------------------|--------------|
| Operating Temperature | -10°C ~ 45°C |
| Humidity | 95% |

Note : Product Specifications and Its Contents Subject to change without any prior notice.

