



ERN-L3665N / ERN-L3665P

Product Features

- 1/3" SONY Effio-E Solution
- Superb Quality 650 TVL Resolution
- 0.5 lux@Day, 0 Lux@ IR On
- 6.0 mm Fixed Lens
- 2-DNR
- OSD Menu, D-WDR
- Electronic Shutter Adjustable, Anti-flicker
- Privacy Zone, Motion Detection, Mirror
- BLC Zones Adjustable
- 36IR Led, Supports Up To 25-30M
- IP66 Waterproof Protection
- Outdoor Wall Mount & Ceiling Mount with Cable Managed Bracket

Technical Specification

Video	ERN-L3665N	ERN-L3665P
Signal System	NTSC	PAL
CCD	1/3" Sony Effio CCD	
Lens	6.0 mm Fixed lens	
Effective Pixel	976 x 494	960 x 582
Horizontal Resolution	650 TVL	
Scanning Frequency (H)	15.734KHz	15.625KHz
Scanning Frequency (V)	59.94KHz	50Hz
Minimum Illumination @ Day	0.5 Lux	
Minimum Illumination @ Night	0 Lux @ IR On	
Gamma	0.45 Default	
S/N Ratio	52 dB	
Video Output	1Vp-p, 75?	
Sync System	2:1 Internal	

Operational	
Lens Adjustment	Auto(Mode & Speed Adjustable) /Manual
Shutter Speed	AUTO / Manual / Anti- Flicker
White Balance	ATW / PUSH LOCK / USER1 / USER2 / ANTI CR / MANUAL /PUSH
AGC	X0.25 ~ X1.00
BLC	Off/ BLC / HLC
ATR-EX(D-WDR)	On/Off (Luminance & Contrast Adjustable)
Day/Night Mode	Auto / Color / B/W / Ext
DNR	2 DNR, On/Off
Motion Detection	ON / OFF, 4 Zone
Privacy Masking	ON / OFF, 4 Zone
OSD Menu	Yes
Mirror	ON/OFF
Scanning Type	2:1 Interlace
Camera ID Name	On/Off

NightVision	
IR LED	36 IR LED
IR Distance	25-30 Meter
IR Wave Length	850nm
Diameter	ø 0.5

Dimensional	
Housing	Outdoor Wall Mount & Ceiling Mount with Cable Managed Bracket
Weight	700g
Dimension	150(L) x 100(H) x 65(W) mm

Electrical Specification	
Power Supply	12V DC
Current Consumption	90mA
IR Consumption	450mA

Environmental	
Operating Temperature	-20°C ~ 50°C
Humidity	95%
Protection Class	IP66

Note : Product Specifications and Its Contents Subject to change without any prior notice.