



ERN-R2147N / ERN-R2147P

Product Features

- 1/3" SONY Super HAD II CCD
- 470 TVL Standard Resolution
- 0 Lux (IR ON)
- 4mm M12 Standard lens
- Auto Electronic Shutter
- Auto White Balance
- Auto Gain Control
- 23IR Led, Supports Up To 15 ~ 20M
- IP66 Waterproof Protection
- Indoor/Outdoor Vandal & Water Resistant Dome

Technical Specification

Video	ERN-R2147N	ERN-R2147P
Signal System	NTSC	PAL
CCD	1/3" SONY Super HAD II CCD	
Lens	4mm M12 Standard lens	
Effective Pixel	512x 492	500 x 582
Horizontal Resolution	470TVL	
Scanning Frequency (H)	15.734KHz	15.625KHz
Scanning Frequency (V)	59.94KHz	50Hz
Minimum Illumination @ Day	1.0 Lux at Day(Cut Off)	
Minimum Illumination @ Night	0 Lux At Night(IR LED On)	
Gamma	0.45	
S/N Ratio	More than 48dB	
Video Output	1V p-p, 75Ω	
Sync System	2:1 Internal	

Operational	
IRIS	Electronically
AGC	Auto
BLC	Auto
Day/Night Mode	Auto
Exposure Mode	AE
Shutter Speed	Auto 1/60~1/100,000sec Auto 1/50~1/100,000sec
White Balance	ATW

Environmental	
Operating Temperature	-10°C ~ 50°C
Humidity	95%
Protection Class	IP 66

NightVision	
IR LED	23 IR LED
IR Distance	20 Meter
IR Wave Length	850nM
Diameter	ø 0.5

Dimensional	
Housing	Vandal Resistant Dome
Weight	350g
Dimension	ø 95* H 75 mm

Electrical	
Power Supply	12V DC Standard ±10%
Current Consumption	80mA
IR Consumption	300mA

Note : Product Specifications and Its Contents Subject to change without any prior notice.

