



ERS-W1030XN / ERS-W1030XP

Technical Specification

Video	ERS-W1030XN	ERS-W1030XP
Signal System	NTSC	PAL
CCD	1/4" SONY SUPER HAD CCD	
Lens	F=3.3 -99.0mm	
Optical Zoom	30X	
Digital Zoom	10X	
Effective Pixel	768 x 494	752 x 582
Horizontal Resolution	Color 540TVL, B/W 570TVL	
Scanning Frequency (H)	15.734KHz	15.625KHz
Scanning Frequency (V)	59.94KHz	50Hz
Minimum Illumination @ Day	0.6 LUX	
Minimum Illumination @ Night	0.005 Lux	
Gamma	0.45	
S/N Ratio	More than 50dB	
Video Output	1V p-p, 75Ω	
Sync System	2:1 Internal	

Pan/Tilt	
Panning Range/Speed	0° to 360° , 300°/s
Tilting Range	0° to 90° , 120°/s
Preset Speed	400° / Sec
PTZ tours	3 Programmable (Pan/Tilt/Zoom and each tour is up to 120sec)
Integrate multi Protocol	Pelco-D/P Selectable
Auto Scan	Smart programmable variable speed
Preset Accuracy	± 0.1°
Preset Point	128
Tour	3
Pattern	6

Product Features

- 1/4" SONY SUPER HAD CCD
- 540 TVL High Resolution
- 0.6Lux/F1.6(color), 0.005Lux/F1.6(Sens-up)
- Lens : F=3.3 - 99.0mm
- 30X Optical Zoom, 10X Digital Zoom
- Auto ICR, SSNR, Digital Effect
- English OSD Menu
- Motion Detection/Privacy Zone
- Mirror Function/Digital Noise Reduction/E-flip
- Task Schedule and Powerful alarm function
- Manual Pan Speed : 0.1° to 300°/s
- Manual Tilt Speed : 0.1° to 120°/s
- Preset Max Speed : 360°/s
- 128 Preset, 3 tour, 6 Pattern
- IP 66 Outdoor Wall Mount
- Standard Wall Mount (Ceiling, Pole & Corner Mount Options)
- Included 24V AC/ 2A Power Adaptor

Operational							
AGC	Low/middle/high/manual/off						
BLC	Low/middle/high/off						
Day/Night Mode	Color, B/W, Auto						
Mirror	On/off						
Motion Detection	On/off						
Privacy Masking	On/off (8 areas)						
Exposure Mode	Auto/manual/anti-flicker						
Shutter Speed	<table border="1"> <tr> <td>Auto</td> <td>Auto</td> </tr> <tr> <td>Fixed 1/120</td> <td>Fixed 1/100</td> </tr> <tr> <td>Auto 1/60 to 1/100000</td> <td>Auto 1/50 to 1/100000</td> </tr> </table>	Auto	Auto	Fixed 1/120	Fixed 1/100	Auto 1/60 to 1/100000	Auto 1/50 to 1/100000
Auto	Auto						
Fixed 1/120	Fixed 1/100						
Auto 1/60 to 1/100000	Auto 1/50 to 1/100000						
SSNR	Low/middle/high/off optional						
White Balance	Auto, ATW, Indoor, Outdoor, Manual						
E-Flip	On/off						

Electrical	
Power Supply	24V AC
Current Consumption	2A
Power Consumption	35W

Environmental	
Operating Temperature	- 10 C - + 50 C
Humidity	95%
Protection Class	IP 66

Dimensional	
Housing	Standard Wall Mount
Weight	6kg
Dimension	334.15(L) x 371.6(H) x 157(Di)mm

Note : Product Specifications and Its Contents Subject to change without any prior notice.