



ERS-W1237XN / ERS-W1237XP

Technical Specification

Video	ERS-W1237XN	ERS-W1237XP
Signal System	NTSC	PAL
CCD	1/4" SONY CCD	
Lens	F=3.3 -129.5mm(F1.6-3.9)	
Optical Zoom	37X	
Digital Zoom	12X	
Effective Pixel	768 x 494	752 x 582
Horizontal Resolution	Color: 550 TVL, B/W: 680 TVL	
Scanning Frequency (H)	15.734KHz	15.625KHz
Scanning Frequency (V)	59.94KHz	50Hz
Minimum Illumination @ Day	0.6 LUX	
Minimum Illumination @ Night	0.005 Lux	
Gamma	0.45	
S/N Ratio	More than 50dB	
Video Output	1V p-p, 75Ω	
Sync System	2:1 Internal	

Pan/Tilt	
Panning Range/Speed	0° to 360° , 300°/s
Tilting Range	0° to 90° , 120°/s
Preset Speed	400° / Sec
PTZ tours	3 Programmable (Pan/Tilt/Zoom and each tour is up to 120sec)
Integrate multi Protocol	Pelco-D/P Selectable
Auto Scan	Smart programmable variable speed
Preset Accuracy	± 0.1°
Preset Point	128
Tour	3
Pattern	6

Product Features

- 1/4" SONY SUPER HAD CCD
- 550 TVL High Resolution
- 0.6Lux/F1.6(color), 0.005Lux/F1.6(Sens-up)
- Lens : F=3.3 -129.5mm(F1.6-3.9)
- 37X Optical Zoom, 12X Digital Zoom
- Auto ICR, SSNR, Digital Effect
- English OSD Menu
- Motion detection/Privacy Zone
- Mirror Function/Digital Noise Reduction/E-flip
- Task Schedule and Powerful alarm function
- Manual Pan Speed : 0.1° to 300°/s
- Manual Tilt Speed : 0.1° to 120°/s
- Preset Max Speed : 360°/s
- 128 Preset, 3 tour, 6 Pattern
- IP 66 Outdoor Wall Mount
- Standard Wall Mount (Ceiling, Pole & Corner Mount Options)
- Included 24V AC/ 2A Power Adaptor

Operational		
AGC	Low/middle/high/manual/off	
BLC	Low/middle/high/off	
Day/Night Mode	Color, B/W, Auto	
Mirror	On/off	
Motion Detection	On/off	
Privacy Masking	On/off (8 areas)	
Exposure Mode	Auto/manual/anti-flicker	
Shutter Speed	Auto Fixed 1/120 Auto 1/60 to 1/100000	Auto Fixed 1/100 Auto 1/50 to 1/100000
White Balance	Auto, ATW, Indoor, Outdoor, Manual	
SSNR	Low/middle/high/off optional	
E-Flip	On/off	

Electrical	
Power Supply	24V AC
Current Consumption	2A
Power Consumption	35W

Environmental	
Operating Temperature	- 10 C - + 50 C
Humidity	95%
Protection Class	IP 66 Outdoor Housing

Dimensional	
Housing	Standard Wall Mount
Weight	6kg
Dimension	334.15(L) x 371.6(H) x 157(Di)mm

Note : Product Specifications and Its Contents Subject to change without any prior notice.